

Magnetic turbine series 4000 meters

Installation/start-up instructions

Introduction

The Turbine Series 4000 is designed for high volume water flow measurement. Produced in sizes from 1 1/2" to 12", it is available in iron or bronze body construction.

Water passes through the meter without a change in flow direction, driving a helical vane rotor in direct proportion to the quantity of water passing through the meter.

Rotor resolutions are converted to engineering units by a gear reduction system, and magnetically coupled to a sealed register. Register calibrated in US Gallons, Cubic Feet or Cubic Meters.

Installation

See document MTR-INS-018 for meter installation instructions.

With MRA 4910 (LRP) low resolution pulser (2 wire)

The transmitting element is a 4-watt rated reed switch, giving a contact closure rate as follows:

	US Gallons	CuFt	M3
1 1/2" – 2"	1 cont/gallon	10 cont/CuFt	1 cont/10 litre
3" – 4"	n/a	n/a	n/a
3" – 8"	1 cont/10 gallons	1 contact/CuFt	n/a
6" – 12"	n/a	n/a	1 cont/100 litre
10" – 12"	1 cont/100 gallons	1 contact/10 CuFt	n/a

To be wired in series with no regard to polarity. Requires power from an external source.

Note: If you use:
 48 VAC, do not exceed .0833 Amps
 24 VAC, do not exceed .1666 Amps
 12 VAC, do not exceed .333 Amps
 6 VAC, do not exceed .6666 Amps

With MRA 4911 (HRP) high resolution pulser (3 wire)

The transmitting element is a slotted disc – opto vane switch, which requires 6-15 VDC power from an external source, giving a contact closure rate as follows:

	US Gallons	CuFt	M3
1 1/2" – 2"	10 cont/gallon	100 cont/CuFt	1 cont/1 litre
3" – 4"	n/a	n/a	1 cont/1 litre
3" – 8"	1 cont/gallon	10 contact/CuFt	n/a
6" – 12"	n/a	n/a	1 cont/10 litre
10" – 12"	1 cont/10 gallons	1 contact/CuFt	n/a

To be wired as follows:
 Red: 6-15 VDC
 White: Output
 Black: Ground VDC

Note: When using the HRP pulser with an R420, a 12 volt Zener Diode (1 watt rated) must be installed in series between 24 VDC out and the red power in line.

With digital register pulsers for all bronze meters to remote counter

Available with plastic (inside) or glass lens (outside). Note: These units are not repairable.

Electrical ratings: Max Voltage 50 VDC
 Max Current 50 mA

The transmitting element is a dry contact reed switch rate at 10 watts.

Duty cycle 50±15% (closed/open)

To be wired in series: Plastic – use black & red connections
 Glass – use black & red wires

See wiring on specification sheet IND-DR-T3000

Contact closure	US Gallons	CuFt	M3
1 1/2" – 4"	1 cont = 10 USG	1 cont = 1 CuFt	1 cont = 100 litres
6" – 12"	1 cont = 100 USG	1 cont = 10 CuFt	1 cont = 1000 litres

About Elster Group

Elster Group is the world's leading manufacturer and supplier of highly accurate, high quality, integrated metering and utilization solutions to the gas, electricity and water industries. In addition, through its subsidiary Ipsen International, it is the leading global manufacturer of high level thermo-chemical treatment equipment.

The group has over 9,000 staff, operations in 38 countries and serves over 115 markets around the world. Elster's high quality products and systems reflect the wealth of knowledge and experience gained from over 170 years of dedication to measuring precious resources and energy.

Elster AMCO Water, Inc.
1100 SW 38th Avenue
Ocala, FL 34478-1852
United States

T +1 800 874 0890

F +1 352 368 1950

watermeters@us.elster.com

www.elster.com

© 2009 by Elster. All rights reserved.

The company's policy is one of continuous product improvement and the right is reserved to modify the specifications contained herein without notice. These products have been manufactured with current technology and in accordance with applicable AWWA Standards.

INS-0005/02-09